WHITE PROTOPET® 1S PETROLATUM

00003009734		
ersion 1.2	Revision Date 2023/03/24	Print Date 2023/03/24
CTION 1. IDENTIFICATION		
Product name : Synonyms :	WHITE PROTOPET [®] 1S PETROI Product code: 216A	LATUM
Manufacturer or supplier's de	t ails Sonneborn, LLC 100 Sonneborn Lane Petrolia PA 16050 United States	
Telephone :	Security (24 hour): (724) 756-2210	0
Emergency telephone numbe	r	
Emergency telephone num- : ber	CHEMTREC: 1-800-424-9300; CC Poison Control Centre: Consult loc emergency number(s).	
Recommended use of the che	mical and restrictions on use	
Recommended use :	High purity Petrolatum is typically a variety of applications including food and general industrial.	
Prepared by :	Product Safety: +1-724-756-2210	
CTION 2. HAZARDS IDENTIFICA	TION	
GHS classification in accorda 1910.1200)	nce with the OSHA Hazard Commu	unication Standard (29 CFI
Not a hazardous substance or m	nixture.	
GHS label elements		

Other hazards

None known.

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or con- firmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture	: Substance
Substance name	: Product code: 216A
CAS-No.	: 8009-03-8



WHITE PROTOPET® 1S PETROLATUM

000003009734

Print Date 2023/03/24

Components

Chemical name	CAS-No.	Concentration (% w/w)
Petrolatum; Petrolatum	8009-03-8	100

SECTION 4. FIRST AID MEASURES

If inhaled	:	Move to fresh air. Artificial respiration and/or oxygen may be necessary. Seek medical advice.
In case of skin contact	:	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized
		skin cleanser. Wash clothing before reuse.
		Seek medical advice.
In case of eye contact	:	Remove contact lenses. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Obtain medical attention.
If swallowed	:	Rinse mouth with water. DO NOT induce vomiting unless directed to do so by a physi- cian or poison control center. Never give anything by mouth to an unconscious person. Seek medical advice.
Most important symptoms and effects, both acute and delayed	:	First aider needs to protect himself.
Notes to physician	:	Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Dry chemical Carbon dioxide (CO2) Water fog Foam
Unsuitable extinguishing media	:	Do NOT use water jet.
Specific hazards during fire- fighting	:	Cool closed containers exposed to fire with water spray.
Hazardous combustion prod- ucts	:	Carbon oxides (CO, CO2), smoke and irritating vapours as products of incomplete combustion.
Further information	:	Prevent fire extinguishing water from contaminating surface water or the ground water system.
Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if nec- essary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

:	Use personal protective equipment.
	Ensure adequate ventilation.
	Evacuate personnel to safe areas.
	Material can create slippery conditions.
	:



Version 1.2

WHITE PROTOPET® 1S PETROLATUM

000003009734

Version 1.2		Revision Date 2023/03/24	Print Date 2023/03/24
		Mark the contaminated area with signs unauthorized personnel. Only qualified personnel equipped with equipment may intervene.	·
Environmental precautions	:	Do not allow uncontrolled discharge of ronment.	product into the envi-
Methods and materials for containment and cleaning up	:	Prevent further leakage or spillage if sa Remove all sources of ignition. Soak up with inert absorbent material. Non-sparking tools should be used. Ensure adequate ventilation. Contact the proper local authorities.	afe to do so.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	:	None known.
Advice on safe handling	:	For personal protection see section 8. Smoking, eating and drinking should be prohibited in the ap- plication area. Use only with adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin, eyes and clothing. Do not ingest. Keep away from heat and sources of ignition. Keep container closed when not in use.
Conditions for safe storage	:	Do not handle at temperatures >40°C, unless wearing appro- priate protective equipment. Store in original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in a dry, cool and well-ventilated place. Keep in properly labelled containers. To maintain product quality, do not store in heat or direct sun- light.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Petrolatum; Petrolatum	8009-03-8	TWA (Inhal- able particu- late matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL

Engineering measures

: No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne



WHITE PROTOPET® 1S PETROLATUM

000003009734

Version 1.2

Revision Date 2023/03/24

Print Date 2023/03/24

contaminants.

Personal protective equip	nt	
Respiratory protection	Use respiratory protection unless adequate local exhau ventilation is provided or exposure assessment demon that exposures are within recommended exposure guid Respirator selection must be based on known or antici exposure levels, the hazards of the product and the sa working limits of the selected respirator.	istrates delines. pated
Filter type	: organic vapour filter	
Hand protection		
Material	: neoprene, nitrile, polyvinyl alcohol (PVA), Viton [®] .	
Remarks	: Chemical-resistant, impervious gloves complying with a approved standard should be worn at all times when ha chemical products if a risk assessment indicates this is essary. When handling hot material, use heat resistant gloves.	andling s nec-
Eye protection	: Chemical splash goggles and a full-face shield should worn when handling this material.	be
Skin and body protection	Choose body protection in relation to its type, to the co tration and amount of dangerous substances, and to th cific work-place.	
Protective measures Hygiene measures	 Wash contaminated clothing before re-use. Remove and wash contaminated clothing and gloves, i ing the inside, before re-use. Wash face, hands and any exposed skin thoroughly af handling. 	

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Colour Odour Odour Threshold	:	Semi-solid. White to light yellow Odourless or mild petroleum oil like. No data available
рН	:	No data available
Melting point/freezing point	:	35 - 80 °C (95 - 176 °F)
Boiling point/boiling range	:	> 230 °C (> 446 °F)
Flash point	:	> 93.4 °C (> 200.1 °F) Method: Pensky-Martens closed cup
Fire Point	:	No data available
Evaporation rate	:	No data available
Flammability		
	•	Remarks: No data available
Auto-Ignition Temperature	:	Remarks: No data available > 554 °F / > 290 °C
Auto-Ignition Temperature Upper explosion limit / Upper flammability limit	-	> 554 °F / > 290 °C

WHITE PROTOPET® 1S PETROLATUM

000003009734

Version 1.2		Revision Date 2023/03/24	Print Date 2023/03/24
flammability limit			
Vapour pressure	:	< 0.1 kPa (68 °F / 20 °C)	
Relative vapour density	:	No data available	
Relative density	:	< 1	
Density	:	0.75 - 0.87 g/cm3 (212 °F / 100 °C)	
Solubility(ies) Water solubility	:	insoluble	
Partition coefficient: n- octanol/water Viscosity	:	log Pow: > 6	
Viscosity, kinematic	:	5 - 30 cSt (212 °F / 100 °C)	
Explosive properties	:	Do not pressurize, cut, weld, braze, so pose containers to heat or sources of	

SECTION 10. STABILITY AND REACTIVITY

Reactivity Chemical stability Possibility of hazardous reac- tions	:	No dangerous reaction known under conditions of normal use. Stable under normal conditions. Hazardous polymerisation does not occur. Stable under normal conditions.
Conditions to avoid Incompatible materials Hazardous decomposition products	:	Heat, flames and sparks. Reactive with oxidising agents. Under normal conditions of storage and use, hazardous de- composition products should not be produced.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

information on interview of exposure				
Eye contact Ingestion Inhalation Skin contact				
Acute toxicity				
Product:				
Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg,		
Acute inhalation toxicity	:	Remarks: No data available		
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 mg/kg,		
Skin corrosion/irritation				
Product:				
Remarks	:	Non-irritating to the skin. Heated material can cause thermal burns.		

Sonneborn[®]

WHITE PROTOPET® 1S PETROLATUM

000003009734

Version 1.2

Revision Date 2023/03/24

Print Date 2023/03/24

SONNEDORN AN HE SINCLAIR BRAND

Serious eye damage/eye irritation

Product:

Remarks

: Non-irritating to the eyes. Heated material can cause thermal burns.

Respiratory or skin sensitisation

Product:

Exposure routes: Skin contact Species: Guinea pig Result: Not a skin sensitizer. Remarks: No evidence of skin sensitization.

Germ cell mutagenicity

Product:

Genotoxicity in vitro	:	Remarks: Not considered to be a germ cell mutagen.
Carcinogenicity		
Product:		
Remarks	:	Classified as non-carcinogenic based on the conditions cited in Nota N (Regulation (EC) 1272/2008, Annex VI, Part 3, Note N).
Reproductive toxicity		
Product:		
Effects on fertility	:	Remarks: Not considered to be toxic to the reproductive system.
Effects on foetal develop- ment	:	Remarks: Not considered to be teratogenic.
STOT - single exposure		
Product:		
Remarks	:	Acute exposure studies show no evidence of systemic toxicity.
STOT - repeated exposure		
Product:		
Remarks	:	Repeat dose toxicity data shows no evidence of target organ toxicity.
Aspiration toxicity		

Product:

Not expected to be an aspiration hazard.

WHITE PROTOPET® 1S PETROLATUM

000003009734

Version 1.2

Revision Date 2023/03/24

Print Date 2023/03/24

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity					
Product:					
Toxicity to fish	:	LC50 (Fish): > 100 mg/l Exposure time: 96 h			
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia (water flea)): > 100 mg/l Exposure time: 48 h			
Toxicity to algae/aquatic plants	:	EC50 (algae): > 100 mg/IExposure time: 72 h			
Toxicity to microorganisms	:	Remarks: No data available			
Persistence and degradabili	Persistence and degradability				
Product:					
Biodegradability	:	Result: Inherently biodegradable.			
Bioaccumulative potential No data available					
Mobility in soil					
No data available					
Other adverse effects No data available					
CTION 13. DISPOSAL CONSIDERATIONS					

SEC

Disposal methods		
Waste from residues	:	The product should not be allowed to enter drains, water courses or the soil. Offer surplus and non-recyclable solutions to a licensed dis- posal company. Waste must be classified and labelled prior to recycling or disposal. Send to a licensed waste management company. Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.
Contaminated packaging	:	Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

National Regulations



WHITE PROTOPET® 1S PETROLATUM

000003009734

Version 1.2

Revision Date 2023/03/24

Print Date 2023/03/24

49 CFR

Not regulated as a dangerous good

When transported above >100C – UN3257 ELEVATED TEMPERATURE LIQUIDS, N.O.S. (9), III, Class: 9 (M9), UN No.: 3257, Packaging Group: III, Hazard No.: 99, Label: 9, Technical Description: Petroleum Jelly, Freight Description Remarks : Road: 65 Petroleum Oil, N.O.I.B.N.

SECTION 15. REGULATORY INFORMATION

EC	ECTION 15. REGULATOR FINFORMATION				
	•		s Substances Reportable Quantity y components with a section 304 EHS RQ.		
	-		s Substances Threshold Planning Quantity y components with a section 302 EHS TPQ.		
	SARA 311/312 Hazards	:	No SARA Hazards		
	SARA 313	:	This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.		
	US State Regulations				
	Massachusetts Right To Kno Petrolatum; Petrolatu		: 8009-03-8		
	Pennsylvania Right To Know Petrolatum; Petrolatu		8009-03-8		
	New Jersey Right To Know Petrolatum; Petrolat	um	8009-03-8		
New York City Hazardous Substances Petrolatum; Petrolatum 8009-03-8					
	California Prop. 65		This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other re- productive harm. For more information go to www.P65Warnings.ca.gov.		
	The components of this prod	luc	t are reported in the following inventories:		
	TSCA	:	All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.		
	AIIC	:	On the inventory, or in compliance with the inventory		
	DSL	:	On the inventory, or in compliance with the inventory		
	ENCS	:	On the inventory, or in compliance with the inventory		
	KECI	:	On the inventory, or in compliance with the inventory		
	PICCS	:	On the inventory, or in compliance with the inventory		




WHITE PROTOPET® 1S PETROLATUM

000003009734

Version 1.2	Revision Date 2023/03/24	Print Date 2023/03/24
IECSC	: On the inventory, or in compliance wi	th the inventory
NZIoC	: On the inventory, or in compliance wi	th the inventory
EINECS	: On the inventory, or in compliance wi	th the inventory
TCSI	: On the inventory, or in compliance wi	th the inventory

SECTION 16. OTHER INFORMATION



Full text of other abbreviations

ACGIH NIOSH REL		USA. ACGIH Threshold Limit Values (TLV) USA. NIOSH Recommended Exposure Limits
OSHA P0		USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim- its for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA P0 / TWA	:	8-hour time weighted average
OSHA Z-1 / TWA		8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency

sonneborn AN HF SINCLAIR BRAND

WHITE PROTOPET® 1S PETROLATUM

000003009734

Version 1.2

Revision Date 2023/03/24

Print Date 2023/03/24

Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization: IECSC - Inventory of Existing Chemical Substances in China: IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Prepared by	:	Product Safety: +1-724-756-2210
Revision Date Date format	-	2023/03/24 yyyy/mm/dd

The information is considered as correct, but not exhaustive, and will be used only as a guide, which is based in the current knowledge of the substance or mixture, and is applicable to proper safety precautions for the product.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN

