

Technical data sheet

MALIC ACID

Version: 09 date: November 2015


Synonyms

2-Hydroxybutanedioic acid; Butanedioic acid, hydroxyl (+/-); Hydroxysuccinic acid.

Formula

$C_4H_6O_5$

Structural formula



Molecular weight: 134.1

CAS number

6915-15-7

EINECS number

230-022-8

EEC number

E296

Product specification

Characteristics	Unit	Value	Method*	Reference
Appearance		White or nearly white crystal	GM037	
Odor and Taste ⁽¹⁾		Characteristic	GM037all01	
Assay	%	99.0 ÷ 100.5	GM005all01	
Malate Test ⁽²⁾		Passes test		
Melting Range ⁽¹⁾	°C	128 ÷ 132	GM027	ASTM D-3417
Fumaric acid	%	1.0 max	GM001all03	
Maleic acid	%	0.05 max	GM001all03	
Residue on Ignition (Sulfated ash) ⁽¹⁾	%	0.1 max	GM015	ASTM D-482
Water insoluble matter ⁽¹⁾	%	0.1 max	GM038	

Characteristics	Unit	Value	Method*	Reference
Heavy metals (as Pb) ⁽¹⁾	ppm	20 max	GM008	
Arsenic ⁽¹⁾	ppm	3 max	GM008	
Lead ⁽¹⁾	ppm	2 max	GM008	
Mercury ⁽¹⁾	ppm	1 max	GM008	
IR Spectrum ⁽¹⁾		Conform to STD	GM006	
Optical (Specific) rotation @ 25°C ⁽²⁾	Degrees	- 0.10 ÷ + 0.10		
Granulometric analysis			GM030	ASTM D-1921
<u>Granular</u>				
• Through 10 mesh sieve	%	100 min		
• Through 50 mesh sieve	%	10 max		
<u>Fine granular</u>				
• Through 25 mesh sieve	%	99 min		
• Through 100 mesh sieve	%	5 max		
<u>Special fine granular</u>				
• Through 40 mesh sieve	%	90 min		
• Through 70 mesh sieve	%	10 max		
<u>Powder</u>				
• Through 60 mesh sieve	%	90 min		
Microbiologic data ⁽³⁾				
• Bacteria	CFU/g	<10		
• Moulds & yeasts	CFU/g	<10		
• Total coliforms	CFU/g	<10		
• Faecal coliforms	CFU/g	<10		
• Salmonella	/25g	absent		

* Internal methods available upon request.

Note: ⁽¹⁾ This is a regular analysis

⁽²⁾ This is a regular analysis performed by an external laboratory

⁽³⁾ This is a regular analysis performed by an external laboratory and does not appear on the Certificate of Quality

Typical properties

Characteristics	Unit	Value
Decomposition temperature	°C	170 ÷ 180
Heat of combustion	Kcal/mol	320
Heat of solution	Kcal/mol	- 4.9
Solubility in water @ 20°C	g/100g	55.5
Viscosity (50% aqueous solution @ 20°C)	mPa.s	6.5
<u>pH vs concentration @ 25°C</u>		
0.1% w/w	2.8	
1.0% w/w	2.4	
3.0% w/w	2.0	
5.0% w/w	1.9	
10.0% w/w	1.8	
20.0% w/w	1.6	
50.0% w/w	0.9	

- The above figures are typical values and are not intended as specification limits

Main applications

Malic acid is mainly used as food additive in beverages, bakery products, confectioneries, desserts, jams and fruit jellies, as preservative in fruit and vegetables and as technological additive in animals feed.

It is also used in the Pharmaceutical and Cosmetic sectors and in a number of typically industrial uses as:

- metal treatment
- textile industry
- plating industry
- retardant for plasters and cements

Polynt malic acid complies with the current edition of **US FCC**, **USP-NF** and **Eu.Ph.** *

It is produced in accordance with

- **FSSC 22000** and it complies with the provision of the **Commission Regulation (EU) No 231/2012** laying down specifications for food additives listed in Annexes II and III to Regulation (EC) No 1333/2008 of the European Parliament and of the Council.
- **FAMI-QS Code of Practice for Feed Additive and Premixture Operators** and it complies with **Regulation (EC) No 1831/2003** for additives used in animal nutrition. **Category:** Technological Additives (cat.1), **Functional Group:** Preservatives (a), Acidity regulators (j).

* available on request



Polynt S.p.A – Scanzorosciate Works
Via Enrico Fermi, 51
I-24020 Scanzorosciate (BG)
Tel. +39 035 652770 – Fax +39 035 652814

Registered Office
Via Enrico Fermi, 51
I-24020 Scanzorosciate (BG)
Tel. +39 035 652111 – Fax +39 035 652421

Malic acid is free from proteins, fibre, starches, vitamins, fats, preservatives, colours, antioxidants or milk products and every product having an animal origin.

It is suitable for the vegetarian, vegan, diabetic, Jewish or Muslim diets.

Polynt malic acid is Kosher certified.

Polynt malic acid is certified Halal by HIA (product code : HIA-ITA-00118-001, HIA-ITA-00118-002, HIA-ITA-00118-003, HIA-ITA-00118-004).

Handling

Packaging: 25 kg or 50 lbs multi-wall paper bags with polyethylene liners;
500/1000 kg big bags;
bulk (40% - 50% solution)

Storage: it must be stored at room temperature, away from open flames or other potential ignition sources, in a dry and well-ventilated place.

Shelf life: 36 months from production date.

The information contained in this sheet is correct and accurate and is based on our technical and scientific knowledge and on literature at the date of going to press. Such information relates only to use of the products in the pure state and for the purposes stated herein. Nothing stated here may be taken or construed as implying of any existing patents. Nor is any warranty, whether explicit or implicit, given with regard to results to be obtained through the use of the aforesaid information.

Safety Data Sheet
Malic acid



Revision 9

01/06/2015 - EN

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Commercial name: **Malic acid**
REACH registration number: 01-2119906954-31-0000
Index number: NOT AVAILABLE
International Chemical Identification: Malic acid
CAS number: 6915-15-7
EC number: 230-022-8

1.2. Relevant identified uses of the substance or mixture and uses advised against

Industrial use:

Intermediates, mixtures and formulated, pH-regulating agents.

Professional use:

Mixtures and formulated, pH-regulating agents, fertilizers, metal surface treatment products, non - metal surface treatment products, flocculant agents, precipitants, neutralization agents, desincrustants, Washing and cleaning products, cosmetics, personal care products, water softeners, water treatment chemicals, Laboratory chemicals.

Consumers use:

Food/feed additives, Cosmetic products, personal care products, Water softeners, Disinfectant, Washing and cleaning products, desincrustant solutions for hemodialysis equipment,

1.3. Details of the supplier of the safety data sheet

Producer: Polynt S.p.A.
Via Enrico Fermi 51
24020 Scanzorosciate (BG)
ITALY
Telephone number: +39 035 652 111
msds@polynt.com

Supplier: Polynt S.p.A.
Via Enrico Fermi 51
24020 Scanzorosciate (BG)
ITALY
Telephone number: +39 035 652 111

1.4. Emergency telephone number

+39 035 652 276

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Reg CE 1272/2008

Hazard statement Code(s)

Serious eye damage/eye irritation
H319: Causes serious eye irritation.

Hazard Class and Category Code(s)

Eye Irrit. 2

2.2. Label elements

Labelling according to Regulation 1272/2008/EC.

Contains: Malic acid
INDEX N° Not available
CAS N° 6915-15-7
EC N° 230-022-8